



SECTION A - A

TECHNICAL DATA		NRCD-15
a)	EXTERNAL DIM. (W x D x H)	1500 x 760 x 1290
b)	GLASS SHELVES (Tier (s))	2
c)	INTERIOR LIGHT (W.) , [Fluo]	36x4
d)	VOLTAGE SUPPLY / AMPERAGE	220 V., 50 Hz., Single phase / 1.1 A
e)	BODY & SIDE PANELS	PUR injection : external cover sheet 19 ga.(1.0 mm.) s/s-304, 2-b finishing.(or as specified.) Internal cover sheet 22 ga. s/s 304 mirrorlike polished surface, Side panel is black color
	SKELETON	Angle steel bar 1-1/2" 6mmt.
	FRONT CURVATURED GLASS	Single pane
	DOOR STRUCTURE	Single pane, Sliding type
	FURNISHING	Door leave(s) is internally filmed with mirrorlike film faced to front.
f)	OPTION	(a)Selectable furnished materials (b) colors (c) bottom glass exclude for not AUS. sales.

## Non-Refrigerated Cake Display Units

<i>WELBILT</i> Manufacturing(Thailand)Ltd.		UNLESS OTHERWISE NOTED		PROJECT:	<b>STODDART (PRIORITY LIST)</b>	P/O NO.
		DESIGN DIMENSIONS ARE IN mm.		PRODUCT:	<b>AS ABOVE SPECIFIED</b>	QTY.
				JOB NO.	ITEM:	DATE: <b>07/03/05</b>
SCALE <b>NTS.</b>	DWG. NO.	PAGE NO.	DRAWN:	CHECKED:	REVISION: <b>D</b>	APPROVED:
SA1:	SA2:	MN1:	MN2:	FM/PD:	AA:	