



| TECHNICAL DATA | | SQHCD-15 |
|----------------|---|---|
| a) | EXTERNAL DIM. (W x D x H) | 1500 x 729 x 1358 |
| b) | TEMPERATURE RANGE / CONTROLLER (s) | 30°C to 110°C |
| c) | BLOWER (Model) | L180 |
| d) | DRY HEATER (Watts) | 3200 |
| e) | S/S WIRE SHELF (Tier) | 3 |
| f) | INTERIOR LIGHT (W.), [Fluo] | 36x4 |
| g) | VOLTAGE SUPPLY / AMPERAGE | 220 V., 50 Hz., Single phase |
| | AMPERAGE | 15.2 |
| h) | BODY | Lower part : PUR injection : external cover sheet 21 ga.(0.8 mm.) s/s-304, 2-b finishing, or as specified. Internal cover sheet is 22 ga.s/s 304 mirrorlike polished surface. |
| | BOTTOM PANEL | PUR panel : cover sheet is 22 ga.s/s-304 (0.6 mm.) |
| | SKELETON | Angle steel bar 1-1/2" 6mmt. |
| | TOP GLASS | Single pane 12 mm.t |
| | FRONT GLASS (Upper display cabinet constructions) | Single pane 8 mm.t , (non heated type), Tempered glass |
| | SIDE GLASS (es) | Single pane 8 mm.t , (non heated type), Tempered glass |
| | DOOR STRUCTURE | Double glazed , Sliding type. |
| i) | OPTION | (a) Selectable furnished materials (b) Colors, (c) Circular adjustable feet |

NOTE :
 - FRONT & SIDE SINGLE PANE TEMPERED GLASS
 - TOP SINGLE PANE - NON TEMPERED GLASS
 - DOUBLE GLAZED GLASS DOOR - TEMPERED GLASS

WELBILT
 Manufacturing(Thailand)Ltd.

UNLESS OTHERWISE NOTED

DESIGN DIMENSIONS ARE IN mm.

PROJECT: **STODDART**

PRODUCT: **SQUARE HOT CABINET DISPLAY UNIT**

P/O NO.

QTY.

DATE: **27/10/06**

SCALE **NTS.** DWG. NO. **SQHCD-15** PAGE NO. **1 OF 1**

JOB NO. ITEM: REVISION: **F**

SA1: SA2: MN1: MN2: FM/PD: APPROVED: